



SILK Breathe Easy



Product Attributes



High Sheen
Premium, rich looking

High Scrub Resistance
Easy washability



Scratch Resistant
Offers ultimate protection to walls, keeps it looking freshly and glossy for years

Formaldehyde Reduction



Pleasant Smell

Kills 99% Bacteria & prevents growth of Fungus & Algae



Environment Friendly
Certified by Singapore Environment Councils "Environmentally Preferred Paint" in accordance to SEC Green Label Council Category 32: Paint and Surface Coating Version 1




Product Description

Silk Breathe Easy Emulsion is a premium interior paint designed to give walls a premium and rich appearance. It is formulated with 100% acrylic emulsions and vibrant pigments together with bio-resistant additives that prevent growth of fungus and algae. The paint retains fresh, glossy look for longer and has low VOC and low smell ensuring users can occupy the room soon after application.

Recommended Use

Plastered surfaces, concrete walls, fibre board, asbestos, gypsum board and false ceiling

Colour Range



Over 2000 Shades

Finish

VERY HIGH

SILKY ✓

SHEEN ✓

MATT

Silky Sheen Finish

Toxicity



No added lead, Chromium(VI), Mercury
VOC Less than 25 gm/lt

Coverage



Approx. 140-160sqft/Lt/2coats
(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats



- **Primer:** Breathe Easy Primer
- **Putty:** For wall / plastered surfaces – Bison Wall Putty/ Happy Wall Putty

Recommended Thinner



Potable water

Recommended Dilution



- **Brush:** 40-50% by volume
- **Roller:** 40-50% by volume

Drying Time



Surface Dry: 15-25 min at 60% RH, 25°C
Hard Dry: 6-8 hours

Gloss Level



600 = 10-16; 850 = 40-50
(depending on shade), measured as per standard test method

Application Method



Roller / Brush

SILK Breathe Easy



Packs



White and PO
Packs of 1, 4, 10 and 20 L

ColorBank
Bases



Fire Hazard Class
Water-based paint,
hence non-flammable



Pot Life of Thinned Material
Use within 24 hours

DIRECTIONS FOR USE

Surface Preparation



Remove all dirt,
loose paint, flakes
using wire mesh



Cover fine cracks with
putty, large cracks may
need cement work



Allow sufficient time
for the putty/cement
work to dry

Priming:

Apply one coat of Breathe Easy Primer. Dilute if needed and dry it overnight.

Direction for Application

Top coat:

Mixwell. Dilute with potable water and apply with brush or roller. Allow it to dry for atleast 6-8 hours or overnight depending ambient temperature, humidity and surface conditions. Apply second coat only when the first coat is dry.

Do not over thin. Do not apply when ambient temperature is below 10°C or more than 40°C.

Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Keep the container tightly closed to prevent drying
- ▶ Use one coat of Bio – Wash for killing fungal growth
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ For deep shade apply one additional coat
- ▶ Do not apply paint on lime washed surfaces and damp wall
- ▶ In case of contact with eyes, wash immediately with water and seek medical help
- ▶ Do not apply paint when ambient temperature is below 10° C or above 45° C

Cleaning Instructions

- Use only toilet soap to clean stains
- To clean oil-based stains, use mineral turpentine oil only
- Use only a soft white cotton cloth for cleaning
- While cleaning, wipe gently without using pressure
- Attempt cleaning the surface only after one week of application

Version No: BPP1/12/2019. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com