

CRACK FILL PASTE



SCIENTIFIC WATERPROOFING SOLUTIONS



Product Attributes




Crack Bridging upto 5mm

Easy Application



Excellent Adhesion

Cohesiveness



Flexibility

Non-Staining



Non-Toxic

Eco Friendly



Product Description

Berger Homeshield Crack Fill Paste is a ready-to-use paste designed to fill and repair surface cracks up to 5 mm. It spreads easily, gives a smooth finish, and provides a strong base for painting. It helps prevent cracks from coming back and keeps walls looking clean and even.

Usase Area

Internal and external plastered, brick, masonry wall cracks of upto 5mm depth & width.

Technical Data

| Properties | Specifications |
|-------------------------|------------------|
| Appearance | White Paste |
| Consistency | Non-sagging |
| Full curing time @ 30°C | 7 days |
| Density | Around 1.40gm/cc |

Product Information

Shelf Life

Best before 3 years from the date of manufacturing in unpacked condition.

Storage

Store in cool and dry place, away from direct sunlight.

Coverage

Approx. 25-30 running mtr/kg

Product Benefits:

- **Crack Bridging** – Crack Bridging up to 5mm ensuring a smooth and uniform finish.
- **Ready to Use** – No mixing required; apply directly with a putty knife.
- **Flexible** – Adjusts to minor wall movements, helping prevent cracks from reappearing.
- **Non-Sagging** – Stays in place without dripping or slumping.
- **Strong Adhesion** – Bonds well to brick, plaster, and concrete surfaces.
- **Eco-Friendly** – Water-based and low in VOCs, making it environmentally friendly.
- **Safe to Use** – Non-toxic and safe to handle with bare hands.
- **Smooth, Paintable Finish** – Can be sanded after drying and painted with polymer-based paints.
- **For Interior & Exterior Use** – Suitable for repairing plaster cracks both inside and outside buildings.

CRACK FILL PASTE



SCIENTIFIC WATERPROOFING SOLUTIONS



Packs



1Kg



Safety Feature
Inflammable



Stability of thinned material
1-1.5 hours



Shelf life
3 years

Directions for Application

- Ensure the surface is clean and free from dust, oil, grease, and loose particles.
- Lightly moisten the surface before application.
- Widen fine hairline cracks to a minimum of 1 mm prior to filling.
- For interior surfaces, remove existing POP or painter's putty until plaster is exposed.
- For porous surfaces, apply a primer coat prepared with Crack Fill Paste & Water in 1:1 over the crack.
- Apply the filler when the surface is tacky, not fully dry.
- Fill cracks and holes using a scraper, putty knife, or trowel.
- Avoid formation of cavities or air bubbles during application.
- Allow to dry for 24 hours before applying a second coat, if required.
- Apply POP or painter's putty only after complete drying.

Safety Instructions:

- Do not use for cracks wider than 5 mm.
- Not suitable for structural cracks, expansion joints, or separation gaps.
- Do not apply on cracks in POP or painter's putty.
- Drying time may increase at temperatures below 10°C.
- Close the container tightly after use.
- Clean tools and hands with soap and warm water immediately after application.
- Keep out of reach of children.
- Refer to MSDS for detailed safety information.

Version No: BPP1/07/2023. Please note that this data sheet supersedes all previous versions.

BERGER JENSON & NICHOLSON (NEPAL) PVT. LTD.

(A wholly Owned Subsidiary of Berger Paints India Limited) B.I.D., Bhaktapur, Nepal, Regd. No. 1643/40
Enquiry/Feedback Contact No: 16600123433/34 (NTC), 9801571001 (NCELL) | Website: www.bergernepal.com