

WEATHERCOAT SMOOTH

EXTERIOR EMULSION



Product Attributes

Truly Durable
Offers 5 years performance warranty



Water repellence
Nano Silicon technology provides protection against extreme rain

Advanced Anti-algae & Anti-fungal protection

Prevents the growth of fungus and algae on exterior walls, ideal for heavy rainfall areas



Dirt pick up resistance
Unique polymer composition helps to remove dust and keeps home looking fresh for years



High-Sheen
Superior sheen finish enhances the beauty and curb appeal of the house



Shades that never fade

Shades lasts for more than 10 years, making your house look new, year after year



Green Pro Certified
Validates our effort in striving towards cleaner, more sustainable future.




Product Description

WeatherCoat Smooth is a 100% acrylic Exterior emulsion that can resist extreme weather conditions. WeatherCoat Exterior Emulsion has been a trusted name built over years of unmatched product performance in the premium range of Paints. It can provide a smooth finishing to exterior walls and withstand extreme weather conditions.

Recommended Use

Exterior plastered surfaces, concrete blocks and asbestos, fiberboards.

Colour Range



Over 2,000 shades

Finish



Smooth

Toxicity



Less than 50 gm/lt

Coverage



65-70sq.ft/ lt/2 coats, under ideal test conditions.
(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats

Primer: For wall/plastered surfaces – WeatherCoat Exterior Primer/Damp Shield Elasto/PU Koat

Putty: For wall/plastered surfaces – Home Shield Waterproof Putty

Drying Time



SD: 30-35 min depending on weather conditions
HD: 4-6 hours

Dilution Ratio



40% by volume
For dark shades: 0-10%

Application Method



Brush/ Roller/ Spray

Gloss Level



12 - 16 at 60° GH When Released

WEATHERCOAT SMOOTH

EXTERIOR EMULSION



Available Packs Sizes:

1 ltr.

4 ltr.

10 ltr.

20 ltr.

ColorBank/ Non-ColorBank – Pack

Bases:

P0, W1, N, N1, N2, Brown, Ivory
and Red/Yellow



Fire Hazard Class
Non- flammable



Pot Life of Thinned Material
Overnight

If the paint comes in contact with eyes or skin, flush with a large amount of water for at least 15 minutes. See a physician, if irritation persists. Wash affected skin areas with soap and water.

Surface Preparation



For fresh/new surfaces: The surface should be allowed to cure properly.



Apply 1 coat of Illusion Sealer to avoid the problem of salt petering.

For Previously Painted Surfaces:



Strip all the old paint and remove all the loose dust, grease, fungus and algae by sanding or wire brushing.



Cracks, holes, dents and damp areas should be repaired properly before painting.



Treat the surface with Biowash solution and wash it next day with potable water. Leave the surface to dry thoroughly.

Priming : Apply 1-2 coats of Damp Shield Elasto. For best results apply WeatherCoat Elastomeric Primer.

Directions for Application

Apply 2-3 coats of topcoat keeping an interval of 4-6 hours between each coat.

Special Note

Before painting, the following things should be checked thoroughly:

- Ideal moisture content of the wall should be below 12%
- Ideal pH value of the wall surface should be between 7-11

Points to Note

- Shake well before use and do not over dilute or over extend brush
- Stir and strain the material through a fine sieve before use
- Do not apply on high alkaline surface
- Do not apply paint on a wet surface
- Do not apply paint on chalking or flaking surface or where the surface is infected with fungus / algae
- Do not apply paint if the ambient temperature is less than or expected to fall below 10°C
- Keep out of reach of children and away from foodstuff
- In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/07/2023. Please note that this data sheet supersedes all previous versions.

BERGER JENSON & NICHOLSON (NEPAL) PVT. LTD.

(A wholly Owned Subsidiary of Berger Paints India Limited) B.I.D., Bhaktapur, Nepal, Regd. No. 1643/40

Enquiry/Feedback Contact No: 16600123433/34 (NTC), 9801571001 (NCELL) |Website: www.bergernepal.com