

# WEATHERCOAT

## ALL GUARD FLEXO



### Product Attributes




#### Truly Durable

Comes with 8 years performance warranty

#### Crack Bridging Ability

The elastomeric film helps cover hair line cracks on the exterior surfaces



#### Water Repellence

Silicon additives provides protections from impact of rain water

#### Superior Dust Pick Up Resistance

Polymer composition doesn't allow dust to settle on the surface



#### High Sheen

Sheen finish enhances the beauty of the house

#### Anti Algal & Anti Fungal

Prevents the growth of algal & fungal for longer period and is ideal for heavy rainfall areas




### Product Description

WeatherCoat Long Life Flexo is a technologically advanced high-performance luxury exterior paint with high sheen and optimised elasticity. The elastic and silicon enhanced water-resistant film of the coating covers hair line cracks and protect the substrate from rains water & dampness. The paint is formulated with superior grade of emulsion with cross-linking technology, light fast pigments and special additives which ensures long term protection of the exterior surfaces from all weather extremities. It has superior dust repellence property and preserves the newly painted look of the house for longer time. The paint comes with 8 years warranty.

### Recommended Use

Exterior plastered surfaces, concrete blocks and asbestos

#### Colour Range



Over 2,000 shades

#### Finish

GLOSS

HIGH SHEEN ✓

SHEEN

MATT

High Sheen

#### Toxicity



### Coverage

70 -75 sq.ft/ lt/2 coats, under ideal test conditions. (Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

### Recommended Undercoats

**Primer:** For wall/plastered surfaces – Use Seal-O-Prime or Damp Shield Elasto or PU Roof Koat

**Putty:** For wall/plastered surfaces – Use Bison Wall Putty or HS Waterproof Putty

#### Drying Time



**SD:** 30 minutes | **HD:** 4-6 hours  
(Drying time varies depending on the climatic conditions such as temperature, relative humidity etc.)

#### Dilution Ratio



40% by volume with water.  
For dark shades 0-10%

#### Application Method



Brush/ Roller/ Spray

#### Gloss Level



12-18 (depends on shade) measured as per standard lab method

# WEATHERCOAT ALL GUARD FLEXO



## Packs



1 Ltr    4 Ltr    10 Ltr    20 Ltr

ColorBank/ Non-ColorBank – Pack



**Fire Hazard Class**  
Non- flammable

**Unusual Fire & Explosion Hazards**  
Material can splatter above 212°F.  
Polymer film can burn.




**Pot Life of Thinned Material**  
Within 24 hrs.

### Health & Safety

If the paint comes in contact with eyes or skin, flush with a large amount of water for at least 15 minutes. See a physician, if irritation persists. Wash affected skin areas with soap and water.

## Surface Preparation



For fresh/new surfaces: The surface should be allowed to cure properly.



Apply 1 coat of Illusion Sealer to avoid the problem of salt petering.

### For Previously Painted Surfaces:



Strip all the old paint and remove all the loose dust, grease, fungus and algae by sanding or wire brushing.



Cracks, holes, dents and damp areas should be repaired properly before painting.



Treat the surface with Bio-wash solution and wash it next day with potable water. Leave the surface to dry thoroughly.

**Priming:** Apply 1-2 coats of Seal O Prime. For Waterproofing - Use 2 Coats of HS Damp Shield Elasto / PU Roof Koat as priming coat.

## Directions for Application

Apply 2-3 coats of topcoat keeping an interval of 4-6 hours between each coat.

### Special Note

Before painting, the following things should be checked thoroughly:

- ▶ Ideal moisture content of the wall should be below 12%
- ▶ Ideal pH value of the wall surface should be between 7-11

### Points to Note

- ▶ Shake well before use and do not over dilute or over extend brush
- ▶ Stir and strain the material through a fine sieve before use
- ▶ Do not apply on high alkaline surface
- ▶ Do not apply paint on a wet surface
- ▶ Do not apply paint on chalking or flaking surface or where the surface is infected with fungus / algae
- ▶ Do not apply paint if the ambient temperature is less than or expected to fall below 10°C
- ▶ Keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/01/2022. Please note that this data sheet supersedes all previous versions.

**BERGER JENSON & NICHOLSON (NEPAL) PVT. LTD.**

(A wholly Owned Subsidiary of Berger Paints India Limited) B.I.D., Bhaktapur, Nepal, Regd. No. 1643/40  
Enquiry/Feedback Contact No: 16600123433/34 | Website: [www.bergernepal.com](http://www.bergernepal.com)